



## **EVO5 DLF** Dryer and Light Finisher

A combined unit featuring **Dryer** and **Light Finisher** sections with a refined software design. Equipped with **6 drying drawers** featuring **Green energy-saving** design, it ensures consistent and uniform drying while reducing power consumption. It includes a drawer for standard **UVA-UVC post-exposure**. For plates up to **132 x 203 cm (52 x 80 inches)**



## EVO COMMON FEATURES

- ▶ **Remote** access (optional)
- ▶ Active **component visualisation** during the process
- ▶ **Manual function** to run the components separately (Service only)
- ▶ Plate process parameters **memory** (up to 24 channels)
- ▶ **Factory Settings** Reset Option
- ▶ **Programmable** warm up / switch off

## HI-TECH FEATURES

- ▶ **Larger** Control Panel
- ▶ New UI: **Simple, clear, intuitive**
- ▶ **Smarter and energy-efficient** Design
- ▶ **Secure data** & parameters backup and **quick recovery** option



## DRYER SECTION

- ▷ **60°** Celsius hot air
- ▷ **6 drawers**
- ▷ **3 sections** with independent control (2 drawers per section)
- ▷ Uniform temperature distribution
- ▷ **Safety thermostat** in every section
- ▷ Integrated exhaust system
- ▷ **Exhaust control** with built-in safety mechanism



## LIGHT FINISHER SECTION

- ▷ **UVA + UVC** lamps for post exposure and light finishing
  - ▷ **Programmable operation:** simultaneous/separate/sequential
    - ▷ **Independent timers** for UVA and UVC
      - ▷ Air flow **cooling system**
  - ▷ Automatic plate cooling with programmable time
    - ▷ Fiber optics for **lamp failure detection**
      - ▷ integrated exhaust system



# evo 5 DLF

## TECHNICAL SPECIFICATIONS



### Dimensions L-W-H



1670 x 2450 x 1170 mm  
65.7 x 96.5 x 49.6 inches

### Power supply



400V 3PH/N/PE 50/60Hz 9.5kW 15A  
230V 3PH/PE 50/60Hz 9.5kW 26A

### Plate thickness



Up to 7 mm / 0.276 inch

### Packaging Dimensions



2700 x 1910 x 1800 mm | 1.410 Kg

### Weight



1040 kg | 2292 pounds

### Maximum plate size



132 x 203 cm | 52 x 80 inches

### Exhaust



1 x 80 mm Ø - 100 m<sup>3</sup>/h  
2 x 140 mm Ø - 600 m<sup>3</sup>/h

### Remote monitoring

Optional

